

Code	Color	SOLAR OPTICAL PROPERTIES				SHGC/G VALUE	
		TS	RS	AS	TV	<i>SINGLE</i> 1/4 CL	<i>INSULATING</i> 1 HA
<b>STYLE 7500 - BLACKOUT</b>							
R13	Ice	0	68	32	0	0.24	0.20
R22	Midnight	0	68	32	0	0.24	0.20
<b>STYLE 7500R - BLACKOUT</b>							
R44	Ice	0	68	32	0	0.24	0.20
R55	Midnight	0	68	32	0	0.24	0.20



PRODUCT CERTIFIED FOR  
LOW CHEMICAL EMISSIONS  
UL.COM/GG  
UL 2818



MIF Seal of Approval



TS = Solar Transmittance  
RS = Solar Reflectance  
AS = Solar Absorptance  
TV = Visual Transmittance

SHGC = Solar Heat Gain Coefficient

1/4 CL = 1/4" Clear Glass  
1 HA = 1" Heat Absorbing Glass

Fabrics Installed Internally  
Zero-Degree Profile Angle

For additional performance values, test references and technical definitions visit us at [www.phifer.com](http://www.phifer.com).

# STYLE 7500 / 7500R SPECIFICATIONS

This attractive blackout fabric maintains high quality at an economical price. Style 7500 is presented in a classic range of neutral colors with a unique PVC-free composition and is ideal for commercial applications. SheerWeave Style 7500 is an excellent option when total light blockage is needed and all Style 7500 colors have an off-white backing.

New Style 7500R, a companion to the Style 7500 range, maintains the same look and feel as its namesake at substantial cost savings and is designed specifically for residential use where commercial fire certifications are not required.

<b>STYLE 7500 FIRE CLASSIFICATION</b>	California U.S. Title 19 (small scale) CAN/ULC-S 109-03 (large and small scale) BS 5867 Part 2 Type B Performance	NFPA 701 TM#1 (small scale) IBC Section 803.1.1 (Class A Rating) NFPA 101 (Class A Rating)
<b>STYLE 7500R FIRE CLASSIFICATION</b>	California Technical Bulletin 117E NFPA 101 (Class A Rating)	
<b>BACTERIA AND FUNGAL RESISTANCE</b>	ASTM E 2180	ASTM G21
<b>ENVIRONMENTAL CERTIFICATION</b>	GREENGUARD	GREENGUARD Gold
	Certified to these standards for low chemical emissions into indoor air during product usage	
<b>LEAD FREE</b>	RoHS/Directive 2002/95/EC ANSI/WCMA A 100.1-2007 for lead content US Consumer Product Safety Commission Section 101	
<b>WARRANTY</b>	5-year interior	
<b>ACOUSTICAL PERFORMANCE</b>	NRC (Noise Reduction Coefficient) and SAA (Sound Absorption Average) tested in accordance with ASTM C423-09a	
<b>UV PROTECTION</b>	Seal of Approval by the Melanoma International Foundation (MIF) for effectiveness in preventing sun damage to the skin or eyes	
<b>CLEANING INSTRUCTIONS</b>	Fabric should be regularly dusted/vacuumed as appropriate. If commercial spot cleaners are used, they must first be tested and allowed to dry on an inconspicuous area to ensure compatibility.	
	<i>Railroading this fabric is not recommended. Colors may vary slightly from swatch samples. All variations are within industry standards.</i>	

STYLE	7500	7500R
<b>WIDTHS</b>	118" 300 cm	118" 300 cm
<b>ROLL LENGTH</b>	30 Linear Yards 27.4 m	30 Linear Yards 27.4 m
<b>COMPOSITION</b>	100% Polyester with Acrylic Coating	100% Polyester with Acrylic Coating
<b>MESH WEIGHT</b>	12.14 oz/yd <sup>2</sup> 412 g/m <sup>2</sup>	12.14 oz/yd <sup>2</sup> 412 g/m <sup>2</sup>
<b>FABRIC THICKNESS</b>	0.014 in 0.356 mm	0.014 in 0.356 mm
<b>OPENNESS FACTOR</b>	Opaque	Opaque
<b>ACOUSTICAL VALUE</b>	NRC .00 / SAA .03	NRC .00 / SAA .03

**PHIFER**  
INCORPORATED

P. O. Box 1700 • Tuscaloosa, Alabama 35403 -1700 USA  
Phone: 205.345.2120 • FAX: 205.391.0799  
Toll Free USA/Canada: 1.800.221.5497  
phifer.com • ISO Registered



© SheerWeave is a registered trademark of PHIFER INCORPORATED.  
™ UL, the UL logos and the UL mark are trademarks of UL LLC.  
Photo courtesy of Hunter Douglas, South America.  
© PHIFER INCORPORATED V18 3033844