

## **SheerWeave 2390 5% & 2360 10%**

<b>Openness Factor:</b>	± 5%	± 10%
<b>UV Blockage:</b>	± 95%	± 90%
<b>Composition:</b>	35% Fiberglass / 65% Vinyl	35% Fiberglass / 65% Vinyl
<b>Mesh Weight:</b>	11.90 oz/yd <sup>2</sup>	18.00 oz/yd <sup>2</sup>
<b>Fabric Thickness:</b>	0.017"	0.017"
<b>Recommended Use:</b>	Interior	Interior
<b>Standard Roll Widths:</b>	63", 98", *126"	63", 98"

### **Additional SheerWeave 2360, 2390, 2410, & 2500 Specifications:**

**Environmental Certification:** GREENGUARD Indoor Air Quality Certified (LEED™)  
GREENGUARD for Children and Schools Certified

**Fire Classification:** M1 (SW2390), California U.S. Title 19  
(small scale), NFPA 701-2004 TM#1 (small  
scale), NFPA 101 (Class A Rating), UBC  
(Class I), BS 5867 2008 Part 2 Type B  
Performance, NFPA 701 TM#2 (large scale),  
and CAN/ULC-S 109-3 (large & small scale)

**Bacteria & Fungal Resistance:** ASTM E 2180, ASTM G22, AATCC30 Part 3,  
ASTM G21, ASTM D 3273, GREENGUARD  
Mold and Bacteria Standard ASTM 6329;  
includes Microban antimicrobial additives

**Lead Free:** RoHS / Directive 2002/95/EC, US Consumer  
Product Safety Commission Section 101,  
ANSI/WCMA A100. 1-2007 for lead content,  
REACH (EC 1907/2006) compliant